

Ampacoll® BK 530

Double-sided butyl rubber strip



- > Double-sided an high quality tape
- > Highly flexible

external
internal

Technical details	Value
Storage	cool and dry
Application temperature	above 0°C
Temperature resistance	-40 to +90°C
Outdoor exposure time	3 months
Resistance to ageing	> 20 years



Jahre Garantie
Ans Garantie
Anni Garanzia
Years Warranty

 **ISO 9001**
Swiss Research

Area of application: Double-sided butyl rubber strip to tape wall membranes, vapour checks and vapour barriers. Also, almost any connections on wood, masonry, concrete, metal, etc. are easy to carry out and durable. Use a primer if necessary!

Delivery forms				
Item no.	Identification	Roll size	Box contents	Pallet details
7640115532954	Ampacoll® BK 530, 15mm	25 m×15mm×1mm	8 rolls = 200 m ¹	60 boxes = 12 000 m ¹
7640115532985	Ampacoll® BK 530, 20mm	25 m×20 mm×2mm	8 rolls = 200 m ¹	32 boxes = 6 400 m ¹

Application photos



Application tips

The surfaces to be sealed must be clean, dry, and free of dust and grease. **Ampacoll BK® 530** seals instantly on the substrate. Stripping the tape from the substrate is only possible to a limited extent. Please note that the staggering of the overlaps must be properly prepared before sealing. When sealing edge connections of wall membranes, vapour check and barriers on porous or dirty surfaces such as concrete,

brick, untreated wood, etc., **Ampacoll® BK 530** should be used with **Ampacoll® Primax** or **Ampacoll® Airmax**



Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Switzerland: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475

www.ampack.biz



The following information may have been superseded by new findings or developments. Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 05.2018