

Ampacoll® Fenax DS

Window connection tape, double-sided



- > Extremely adhesive
- > Full-surface adhesive
- > Adhesive on both sides
- > Moisture variable
- > One and the same tape can be used inside and outside. The "tighter inside than outside" requirement is met.
- > Easy-peel liner

Technical details		Value	Standard
S _d value		1.5 – 16.5 m	
Amount of adhesive to be applied		300 g/wm ²	
Application temperature		-5 °C to +40 °C	
Temperature resistance		-40 °C to +100 °C	
UV stability		12 months (Central Europe)	
Tear resistance	lengthwise	220 N/5 cm	EN 12311-2/A
	cross	280 N/5 cm	
Elongation at break	lengthwise	100 %	EN 12311-2/A
	cross	140 %	

10
 Jahre Garantie
 Ans Garantie
 Anni Garanzia
 Years Warranty




Joint properties as per ift guideline MO01/1: 2007 – Section 5
 18_002878_PRO3
 (PB_E03_020310-en)


ISO 9001
 Swiss Research


Area of application: For sealing doors and windows in solid, wood and metal constructions **before** installation.

Delivery forms				
Item no.	Identification	Roll size	Box contents	Pallet contents
7640115537515	Ampacoll® Fenax 30/45 DS	25 m × 75 mm Liner division: 30 mm, 45 mm	6 rolls = 150 metres	49 boxes
7640115537546	Ampacoll® Fenax 30/70 DS	25 m × 100 mm Liner division: 30 mm, 70 mm	4 rolls = 100 metres	49 boxes
7640115537607	Ampacoll® Fenax 30/170 DS	25 m × 200 mm Liner division: 30 mm, 170 mm	2 rolls = 50 metres	49 boxes



 Please observe our installation instructions for our window products.

 Please observe the recommendations for use and further system products in our adhesives matrix.

 Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Swiss: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475



The following information may have been superseded by new findings or developments. Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 12.2022

8007EU/DX.YY(VS)1222

www.ampack.biz