Technical data sheet

Ampacoll® Fenax DS

One side is fully adhesive, the other has a fleece layer with a 30 mm wide adhesive strip attached to it. This window connection tape is ideal for creating tight connections of windows or doors before installation.

- Fully adhesive on one side
- Extremely adhesive even at low temperatures
- Moisture variable
- Same tape for both inside and outside use The «tighter inside than outside» requirement is met
- Split finger-lift liner
- Can be plastered over
- Natural weathering period: 12 months

Technical details	Value	Standard
S_d value	1.5 m to 16.5 m	EN 1931
Tear resistance longitudinal | transverse	220 N/5 cm | 280 N/5 cm	EN 12311-2/ A
Tear elongation longitudinal | transverse	100 % | 140 %	EN 12311-2/ A
Temperature resistance	-40 °C to 100 °C	
Durability	> 20 years	
Storage conditions	cool and dry	
UV stability	12 months	
Working temperature range	-5 °C to 40 °C	

Aktuelle Verlegeanleitung
Instructions de pose actuelles
Current installation instructions
Istruzioni di posa aggiornate

20-YEAR PREMIUM WARRANTY

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C

© ift Rosenheim

phA CERTIFIED COMPONENT Passive House Institute

GEV-EMICODE EC2 low emission