

Ampacoll® Hybrix

Sealant and levelling compound



- > Permanently elastic
- > Weather and UV-resistant
- > Adheres without primer even on damp substrates
- > Free from solvents, isocyanate and silicone

Technical details

Storage	cool and dry
Application temperature	from 0°C
Temperature resistance	-40°C to +90°C
Skin formation	approx. 10 minutes
Curing speed	2mm in the first 24 hours

10
Jahre Garantie
Ans Garantie
Anni Garanzia
Years Warranty



CE
15651-1

ISO 9001
Swiss Research

Area of application: For filling imperfections (cracks, unsealed bed joints, not void-free concrete, chipped bricks, etc.) or sealing geometrically challenging areas such as corners or window connection profiles (FBA). Observe the “tighter inside than outside” principle.

Delivery forms

Item no.	Identification	Contents	Box contents
7640115538444	Ampacoll® Hybrix cartridge	290 ml	12 cartridges
7640115538475	Ampacoll® Hybrix tubular bag	600 ml	12 tubular bags

System accessories



Ampacoll® Fenax
Window connection tape

external
internal



Ampacoll® Sillskin
Parapeet covering /
windowsill base

external
internal



Ampacoll® Komprimax K
Precompressed
joint sealing tape

external
internal



Ampacoll® Komprimax M
Precompressed
multifunctional tape

external
internal



Please observe our
installation instructions for
our window products.



Please observe the recommenda-
tions for use and further system
products in our adhesives matrix.



Further information and
detailed documentation at
www.ampack.biz

Sales via specialist dealers

Ampack Swiss: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475

www.ampack.biz



The following information may have been superseded by new findings or developments.
Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 05.2019

8010EU/DX.YY(VS)0519