

Ampacoll® ND.Band

Nail sealing tape for roofs and formwork strips



- Better adhesion than many customary nail sealing products
- Closed-cell foam, PVC free
- Optimum width – fits all counter battens
- HFA leak detection tests (Holzforschung Austria)

Technical details

Shelf life	2 years
Storage	Cool and dry
Application temperature	from 0 °C
Resistance to temperature	-25 °C to +75 °C
Outdoor weathering period	3 months
Resistance to ageing	> 20 years

Area of application: Self-adhesive nail sealing tape for roofs and formwork strips. Prevents humidity from penetrating the construction. Particularly suitable for flat roof coverings as the tape creates a seal.

10

Jahre Garantie
Ans Garantie
Anni Garanzia
Years Warranty

Security is part of the system at Ampack. We not only cover the cost of the materials, but also the installation and removal costs.

✓ **HFA-tested**

Leak detection tests of Holzforschung Austria

ISO 9001
Swiss Research

Delivery forms

Item no.	Identification	Roll size	Box contents	Pallet contents
7640115530202	Ampacoll® ND.Band 60	30 m × 60 mm × 3 mm	8 rolls = 240 m ¹	18 boxes
7640115536389	Ampacoll® ND.Band 80	30 m × 80 mm × 3 mm	6 rolls = 180 m ¹	18 boxes
7640115537027	Ampacoll® ND.Band 70	30 m × 70 mm × 3 mm	7 rolls = 210 m ¹	18 boxes



Other nail sealing products



Ampacoll® ND 60:
Nail seals, 60 mm wide



Ampacoll® ND 80:
Nail seals, 80 mm wide



Ampacoll® ND duo
Nail sealing tape adhesive on both sides



Application tips

The protective function of a nail seal

What good is the best roof membrane when water can penetrate the screw or nail holes? **Ampacoll® ND.Band** nail sealing tape is your guarantee for water-tight roof membranes. Twisted counter battens, shrinking wood, extreme alternating cycles of wet and dry, low contact pressure, poor adhesion of the nail in the rafters, mechanical loading from scaffolding or tile trestles, permanent snow coverings – these are all potential sources of damage!

Tips when laying

Make a chalkline for every counter batten and stick the **Ampacoll® ND.Band** directly onto the roof membrane. For wide roof lathing **Ampacoll® ND.Band 80**. Then mount the counter battens. The nail sealing tape can often replace the chalkline.

Ampack recommends

Counter battens are extremely susceptible to the extremes of wet and dry. Therefore for better insulation a nail seal is preferred to screwing the counter battens.




Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers



The following information could have been superseded by new findings or developments. Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 03.2018

www.ampack.biz
Ampack Switzerland: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475

