Ampatex® Ombrello

Self-adhesive vapour check and weather protection





- > Transparent: furring, chalklines, penetrations, etc. remain visible
- > Adhesive made of UV acrylate: moisture does not affect the adhesive
- Natural weathering period of 3 months: sufficient time for construction phase
- > Easy to install and non-slip: for faster work and safe walking during the construction phase

Technical details		Value	Standard
s _D value		5 m	EN 12572
Weight		160g/m² (± 10%)	EN 1849-2
Tear resistance	longitudinal transverse	110N/5cm 100N/5cm	EN 12311-2
Tear elongation	longitudinal transverse	60% 80%	EN 12 311-2
Resistance to further tearing (nail shaft)	longitudinal transverse	80 N 80 N	EN 12310-1
Fire performance		E	EN 13 501-1
Waterproofing at 2 kPa		passed	EN 1928
Width of overlap		≥10 cm	
Straightness		<75 mm/10 m	EN 1848-2
Temperature resistance		-40°C -+80°C	
Remains durable after artificial ageing		passed	EN 1296
Outdoor weathering, pitched roof >10° and wall		3 months	
Outdoor weathering, ceiling		1 month	

Area of application: Transparent, full-surface adhesive vapour check and weather protection membrane. Used, for example, to temporarily cover wooden ceilings during the transport, assembly and construction phase or to ensure airtightness on wooden materials and other substrates.











*Conditions for the twenty-year premium warranty include registering the building object and the Ampack products used. In addition, our products must be used as part of a system. For further details, please see our General Warranty Conditions.

Delivery forms					
Item no.	Identification	Roll dimensions	Pallet contents		
7640442091384	Ampatex® Ombrello	1,5 m × 50 m = 75 m2 Liner division: 25 cm/125 cm	28 rolls = 2100 m ²		













Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers









