

Tendering text: Ampatex Ombrello Weather protection / construction period cover, fully self-adhesive

item	Description of service		
1	General information		
	This weather protection and construction period cover, which also serves as an airtight layer and is bonded over the entire surface, is positioned on the warm side of the thermal insulation. All overlaps and connections must be airtight. Any damage to the area or unavoidable holes must be sealed. Technical details:		
	Roll size:	1.5 m x 50 m	
	s _D value:	3.5 m	
	Weight:	130 g/m2	
	Fire index:	RF 3(cr), VKF	
	Fire behaviour:	E, EN 13501-1	
	Natural weathering period:	,	
	Steep-pitched roof >10° and wall	3 months	
	Ceiling	1 month	
	CE marking:	EN13984:2013	
	furring, with overlaps at least 10 cm wide or along the overlap line. Ampatex Ombrello must be bonded airtight over the entire surface and without creases to a clean and dry surface. Seal any nail or screw heads on roof battens or similar <10° DN with Ampacoll BK 535 nail seal, for >10° DN with Ampacoll ND or nail sealing tapes Ampacoll ND.Band or Ampacoll ND duo.		
	Roof shape:		
	Roof pitch:		
	Quantitym² Price per unit Total price		
3	Edgings / edge connections		
3.1	Edgings / edge connections on chimneys, perimeter walls, etc. using Ampacoll Flexx Pro flexible adhesive tape.		
	Quantitym Price per	unit Total price	

4	Penetrations			
4.1	Tape over penetration connections such as outlet vents, chimneys, etc. with Ampaco butyl rubber strip, 2 x 50 mm or 2 x 80 mm, for an airtight and rainproof seal. Alternative use for straight/angular penetrations: Ampacoll Flexx Pro 150			
	Quantityunits Price per unit	Total price		
4.2	Total edge length < 50 cm			
	Quantityunits Price per unit	Total price		
4.3	Total adga langth > 50 cm to 100 cm			
4.3	Total edge length > 50 cm to 100 cm			
	Quantityunits Price per unit	Total price		
4.4	Total edge length > 100 cm to 200 cm (penetrations with a total edge length of more than 200 cm are considered edgings / ecconnections and are indicated there).			
	Quantityunits Price per unit	Total price		
4.5		all Claus Des flavible adhesive tons		
4.5 Roof windows or other flat penetrations using Ampacoll Flexx Pro flexible adhesive		oli Flexx Pro llexible adriesive tape.		
	Alternative option:			
	Quantity Price per unit	Total price		
5	Pre-treatment of unsuitable surfaces (supplementary to item 4)			
5.1	For connections on porous, dusty or rough backings such as masonry, concrete, raw wood, etc., a primer coat of Ampacoll Primax or Airmax must be applied.			
	Quantity Price per unit	Total price		

6 Sources and documentation

All product data and application tips can be found in the product inserts.

Further information and sources: Ampack AG Seebleichestrasse 50 CH-9401 Rorschach Tel. +41 71 858 38 00

Fax +41 71 858 38 37

E-mail: ampack@ampack.ch

www.ampack.ch

Note

Considerations in terms of content

Users will occasionally have to make changes to adapt to a specific situation. Similarly, suggestions for tendering texts can only cover standard situations. Custom solutions must be worked out for special circumstances. In its manufacturing process, Ampack AG places an emphasis on state-of-the-art technology and follows established practices in the construction industry as well as all applicable standards and statutory provisions. In the event of doubt, the details provided in the documentation or booklets/fliers published by Ampack AG are definitive.

Legal considerations

The drafting of tendering texts is a voluntary extra service provided free of charge by Ampack for the purposes of aiding architects, planners and fabricators. It is carried out to the best of our knowledge, but to the express exclusion of any liability arising from the provision of advice. See the General Terms and Conditions of Ampack AG for information in this regard.

Authorisation for use by customers of Ampack AG

The tendering texts are authorised for use by our customers (architects, planners and fabricators) for their own purposes. Sharing or publication of these texts in printed or electronic media is not permitted. Constructive comments and additions are welcomed by the author. In order to facilitate transcription to a tendering platform, unnecessary formatting has been avoided.

Ampack AG Marius Schorer Head of application technology Seebleichestrasse 50 CH-9400 Rorschach Tel.: +41 (0) 71 858 38 00

Fax.: +41 (0) 71 858 38 37 m.schorer@ampack.ch

Copyright Ampack AG, CH-9400 Rorschach 19 August 2022