

Tender text: Ampatex Variano 3
 For use as an airtight layer
 when renovating roofs from outside.



Item	Instructions
------	--------------

1	<p>General</p> <p>The vapour check also serves as an airtight layer. When renovating from outside, the requirements regarding outdoor weathering must be observed. All joints, gaps, overlaps and connections must be airtight and rainproof. Air pockets must be avoided. Any damage to the surface or unavoidable holes must be sealed. Moisture-variable products are not suitable for use on temporary roofs. We recommend appropriate weather protection measures.</p>
---	--

Technical details:

Roll size:	1,5 m x 50 m / 3,0 m x 50 m
s _D value:	0.8 m – 60 m
Weight:	90 g/m ²
Fire behaviour:	E, EN 13501-1
CE marking:	EN13984:2013

2	<p>Ampatex Variano 3 vapour check is delivered and applied on the existing underlying structure and along the sides and over the rafters. Smooth, printed side must face up. The ends must overlap 10 cm. Tacks or nails must be covered by the overlapping ends. Use Ampacoll XT to bond the overlapping ends together and create an airtight and rainproof seal.</p>
---	--

Quantity.....m² Unit price.....Total price.....

3	<p>Underlying structure</p> <p>Use soft wood fibre boards (thick enough to walk on) if components are not suitable for vapour checks to be installed directly on the underlying structure (risk of damage). Can simultaneously serve as installation surface.</p>
---	--

Quantity.....m² Unit price.....Total price.....

4	<p>Installation aid</p> <p>Secure Ampatex Variano 3 with Ampacoll DT double-sided adhesive tape (0.3 x 20 mm) on underlying structures that cannot be nailed (metal sections, etc.)</p>
---	--

5	<p>Lateral attachment to rafters</p> <p>Lateral attachment to rafters (ideally with backing strip) to avoid convection and air pockets.</p>
---	--

Alternative:

Use Ampacoll® DT double-sided adhesive tape on smooth and full-squared rafters.

Use Ampacoll® Superfix liquid adhesive on rough, round or cracked rafters.

Quantity.....lfm Unit price..... Total price.....

6 Edge connections
Use Ampacoll BK 530 adhesive (2 x 20 mm) to create an airtight seal with components with a smooth, dust-free surface (planed wood, plastic sections, metal, etc.) and porous and rough surfaces (tiles or concrete wall, untreated wood, etc.). Apply Ampacoll Primax or Airmax on porous, dusty or rough surfaces.

Alternative: Use Ampacoll Superfix liquid adhesive.

Quantity.....lfm Unit price..... Total price.....

7 Breakthroughs
Seal breakthrough connections at ventilation or electrical conduits, purlins, rafters etc. airtight with butyl rubber tape Ampacoll BK 535, 2 x 50 mm or 2 x 80 mm. Prime porous, dusty, or rough surfaces with Ampacoll Primax.

Quantity.....rm Unit price..... Total price.....

7.1 Unwinding < 50 cm

Quantity.....Piece Unit price..... Total price.....

7.2 Unwinding > 50 cm to 100 cm

Quantity.....Piece Unit price..... Total price.....

7.3 Unwinding > 100 cm to 200 cm
(Openings with unwinding of more than 200 cm are considered edge connections and are listed there.)

Quantity.....Piece Unit price..... Total price.....

8 Supplier and documentation
Please refer to the product inserts for all product specifications and application tips.

Additional information and suppliers:

Ampack AG
Sebleichstrasse 50
9401 Rorschach
Tel. +41 71 858 38 00
Fax +41 71 858 38 37
www.ampack.eu
ampack@ampack.ch

Note

Content considerations

Adjustments by the user will remain necessary on occasion. Texts for tender proposals describe standard situations only. Special cases must be considered separately. When carrying out the creation, Ampack AG is guided by the best available technology, the recognised rules of the building trade, association requirements and current standards and regulations. In the event of doubt, the details in the documentation or in the brochures and flyers of Ampack AG apply.

Legal considerations

The preparation of texts for invitations to tender is a voluntary, non-payable additional service of Ampack, and is intended as an aid for architects, planners and processors. It is carried out to the best of the company's knowledge, but expressly excludes any liability derived from consulting services. See the General Terms & Conditions of Ampack AG for further information.

Permission for use by customers of Ampack AG

The texts for invitations to tender can be used by our customers (architects, planners and processor) for their own purposes. Any disclosure or publication in printed matter or electronic media is not permitted. Constructive criticism and amendments are expressly requested and welcomed by the author. To facilitate the transfer to tender proposals, unnecessary formatting has been omitted.

Ampack AG
Ulrich Höing
Head Technology and Development
Seebleichstrasse 50
CH-9400 Rorschach
+41 71 858 38 00 Tel
+41 71 858 38 37 Fax
ulrich@ampack.ch

Copyright Ampack AG, CH-9400 Rorschach

Last updated: 16.03.2018