



Tendering text: Ampatop F black Membrane for façade with open gaps

Position	Description
----------	-------------

1 General
Façade membranes prevent the flow of cold, outdoor air through thermally insulated constructions; this means that all joints, gaps, overlaps and connections must be made windproof. Damage to the surfaces must be avoided and penetrations must be made windproof.

Technical data:

Roll dimensions:	1,5 m x 50 m / 3,0 m x 30 m
Ampatop F black plus:	With integrated tape
s _D value:	0,09 m
Weight:	200 g/m ²
Fire behaviour:	E, EN 13 501-1
Outdoor weathering:	3 months (before installation of the façade cladding)
UV stability:	>10 years
CE marking:	EN 13859-2:2014

2 Support structure
Preparation or completion of the support structure of component where a façade membrane cannot be directly attached to the existing structure.

Quantity.....m² Unit price..... Total price.....

3 Supply and laying of the façade membrane Ampatop F black
The façade cladding should be installed as soon as possible, at the very latest within 3 months. The joint width may be up to 3 cm. The individual façade elements selected should be twice as wide.

Proper installation of the membrane in accordance with the manufacturer's instructions. Ampatop F black should be laid on to the existing support structure, taut and without any folds, with the black side outwards. It should be fastened with staples that must be invisible in the overlap area. It is advantageous to cover them with battens. Both the vertical and the horizontal overlaps should be 15 cm wide and bonded with Ampacoll UV to make them windproof. Thoroughly press the glued areas. Next the counter battens are laid, thus fixing the wind proofing to the support structure. Visible staples that are exposed to the weather could lead to leaks and as such should be avoided. We recommend fixings that are at least galvanized, with stainless steel being preferable.

Quantity.....m² Unit price..... Total price.....

4 Sealing work (supplement to Position 3)

4.1 Edgings

Edgings to adjoining structures, such as smooth, dust-free window frames, etc., should be bonded with Ampacoll UV or Ampacoll Superfix to make them windproof. Connection widths should be at least 10 cm. If this is not possible, then they should be secured mechanically.

Quantityrm Unit price..... Total price.....

4.2 Penetrations

Penetration connections, to ventilation or electrical pipes, purlins, rafters, etc., should be bonded with Ampacoll UV or Ampacoll Superfix to make them windproof. If Ampacoll UV is used on porous, dusty or rough surfaces, then an undercoat of Ampacoll Airmax or Primax should be applied.

Quantityrm Unit price..... Total price.....

4.3 Connections to windows and external doors

Ampatop F black should be made windproof with Ampacoll UV or Ampacoll Superfix on the frame and should be mechanically secured if necessary.

Quantityrm Unit price..... Total price.....

4.4 Unwinding < 50 cm

Quantity.....units Unit price..... Total price.....

4.5 Unwinding > 50 cm bis 100 cm

Quantity.....units Unit price..... Total price.....

4.6 Unwinding: >100 cm to 200 cm

(Penetrations with an execution of more than 200 cm are considered to be flashings and are listed under these.)

Quantity.....units Unit price..... Total price.....

5 Preparation of unsuitable surfaces (supplement to Position 4)

When using Ampacoll UV, connections on porous, dusty or rough surfaces, such as masonry, concrete, bare wood, etc., should be primed with Ampacoll Airmax or Primax.

6 Sources and documentation

The entire product data and processing instructions can be found under the technical documentation of the Ampack company.

Additional information and suppliers:

Ampack AG
Seebleichstrasse 50
9401 Rorschach
Tel. +41 71 858 38 00
Fax +41 71 858 38 37
www.ampack.eu
ampack@ampack.ch

Note

Content considerations

Adjustments by the user will remain necessary on occasion. Texts for tender proposals describe standard situations only. Special cases must be considered separately. When carrying out the creation, Ampack AG is guided by the best available technology, the recognised rules of the building trade, association requirements and current standards and regulations. In the event of doubt, the details in the documentation or in the brochures and flyers of Ampack AG apply.

Legal considerations

The preparation of texts for invitations to tender is a voluntary, non-payable additional service of Ampack, and is intended as an aid for architects, planners and processors. It is carried out to the best of the company's knowledge, but expressly excludes any liability derived from consulting services. See the General Terms & Conditions of Ampack AG for further information.

Permission for use by customers of Ampack AG

The texts for invitations to tender can be used by our customers (architects, planners and processor) for their own purposes. Any disclosure or publication in printed matter or electronic media is not permitted. Constructive criticism and amendments are expressly requested and welcomed by the author. To facilitate the transfer to tender proposals, unnecessary formatting has been omitted.

Ampack AG
Ulrich Höing
Head Technology and Development
Seebleichstrasse 50
CH-9400 Rorschach
+41 71 858 38 00 Tel
+41 71 858 38 37 Fax
ulrich@ampack.ch

Copyright Ampack AG, CH-9400 Rorschach

Last updated: 15.05.2017