

Tendering text: Ampatop Protecta / Protecta plus
Roof membrane



Item	Service specification
------	-----------------------

1 General information
 Ampatop Protecta / Protecta plus perform in connection with Ampacoll system adhesive technology as a roofing membrane.

Technical data:
 Roll dimensions: 1.5 m x 50 m / 3.0 m x 50 m
 Ampatop Protecta plus: integrated tapes on both sides
 s_D value: 0.1 m
 Weight: 190 g/m²
 Resistance against water penetration: W1
 Outdoor exposure time: 3 months
 Minimum roof incline: 10°
 Fire reaction: E, EN 13501-1
 CE label: EN13859-1:2014

2 Supply and lay the Ampatop Protecta / Protecta plus roof membrane on the existing supporting structure, parallel to the eaves.

All joints must have an overlap of 10 cm, in the overlap area use conceal brackets (wide head nails) and glue the overlaps with Ampacoll XT, 60 mm or integrated tape to protect against rain. Lowest sheet placed on inflow sheet, top sheet pulled over the roof ridge.

Transverse joints must also overlap 10 cm and be glued with weather-proof Ampacoll XT, 60 mm. Grind the glued joint thoroughly.

Seal the nail and screw positions of the counter lathing with nail-sealing Ampacoll ND, nail-sealing tape Ampacoll ND.Band or Ampacoll ND duo.

Roof incline:.....
 (minimum roof incline 10°)

Roof shape:.....

Quantity.....m² Unit price..... Total price.....

3 Sealing work (surcharges for Item 2)

3.1 Boarding slats
 Boarding slats on chimneys, roof windows and other installations must have a minimum height of 15 cm and be glued with Ampacoll BK 530, 2 x 20 mm, and secured mechanically if required.

Alternatively, use Ampacoll Superfix liquid glue

Quantity.....rm Unit price..... Total price.....

3.2 Edge connections
Connections to inflow sheets must be glued with Ampacoll Superfix.

Quantity.....rm Unit price..... Total price.....

3.3 Intersections
Intersection connections such as outlet vents, chimneys, etc., must be protected against wind and rain with butyl rubber tape Ampacoll BK 535, 50 mm or 80 mm.

Alternatively, use Ampacoll Superfix

Quantity.....rm Unit price..... Total price.....

3.4 Unwind < 50 cm

Quantity.....Units Unit price..... Total price.....

3.5 Unwind > 50 cm to 100 cm

Quantity.....Units Standard price..... Total price.....

3.6 Unwind: >100 cm to 200 cm

(Intersections with a unwind of more than 200 cm are regarded as boarding slats and are stated there)

Quantity.....Units Unit price..... Total price.....

3.7 Protect roof windows or other flat intersections against wind and rain with strips of Ampatop Protecta / Protecta plus with double-sided butyl adhesive tape Ampacoll BK 530, 2 x 20 mm.

Alternatively, use Ampacoll Superfix.

Quantity.....Units Standard price..... Total price.....

4. Pre-treatment of unsuitable surfaces (surcharge to Item 3)
Pre-treat connections and bondings on porous, dusty or rough surfaces such as masonry, concrete, untreated wood, etc, with Ampacoll Primax or Airmax.

5. Supplier and documentation
All product data and handling instructions can be obtained from the technical documentation of the Ampack company.

Additional information and suppliers:

Ampack AG
Seebleichstrasse 50
9404 Rorschacherberg, Switzerland
Tel. +41 (0)71 858 38 00
Fax +41 (0)71 858 38 37
E-mail: ampack@ampack.ch
www.ampack.eu

Note

Content considerations

Adjustments by the user will remain necessary on occasion. Texts for tender proposals describe standard situations only. Special cases must be considered separately. When carrying out the creation, Ampack AG is guided by the best available technology, the recognised rules of the building trade, association requirements and current standards and regulations. In the event of doubt, the details in the documentation or in the brochures and flyers of Ampack AG apply.

Legal considerations

The preparation of texts for invitations to tender is a voluntary, non-payable additional service of Ampack, and is intended as an aid for architects, planners and processors. It is carried out to the best of the company's knowledge, but expressly excludes any liability derived from consulting services. See the General Terms & Conditions of Ampack AG for further information.

Permission for use by customers of Ampack AG

The texts for invitations to tender can be used by our customers (architects, planners and processor) for their own purposes. Any disclosure or publication in printed matter or electronic media is not permitted. Constructive criticism and amendments are expressly requested and welcomed by the author. To facilitate the transfer to tender proposals, unnecessary formatting has been omitted.

Ampack AG
Ulrich Höing
Head Technology and Development
Seebleichstrasse 50
CH-9400 Rorschach
+41 71 858 38 00 Tel
+41 71 858 38 37 Fax
ulrich@ampack.ch

Copyright Ampack AG, CH-9400 Rorschach

Last updated: 19.10.2016