

Ampatop® SealEdge

Eaves membrane



- > Prefabricated combination of **Ampatop® Seal** and a high-quality UV-resistant PVC strip
- > Can be solvent welded or hot welded

Technical details		Value	
Weight	Ampatop® Seal	350g/m ²	
	PVC strip	650g/m ²	
Width	Ampatop® Seal	300 mm	
	PVC strip	300 mm	
Tear resistance	Ampatop® Seal	lengthwise	350
		crosswise	380N/5cm
	PVC strip	lengthwise	2800
		crosswise	2500N/5cm
Welding temperature	Ampatop® Seal	240–280 °C	
	PVC strip	280 °C	
UV stability	Ampatop® Seal	3 months	
	PVC strip	>10 years	



 **ISO 9001**
Swiss Research

Area of application: Ampatop® SealEdge is a prefabricated eaves membrane with a UV-resistant PVC strip welded to an **Ampatop® Seal roof membrane**. The product is used to seal open eaves with perforated metal to drain water from the roof membrane into the gutters.

Delivery forms		
Item no.	Identification	Roll size
7640115536945	Ampatop® SealEdge	600 mm × 30 m



Please follow the recommendations for use and consider other system products in our adhesives matrix.



Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Switzerland: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475

www.ampack.biz

The following information may have been superseded by new findings or developments. Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 05.2018

